

07-07-00

A

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of Laurent POUGET ; Thierry GOURLOT

Filed: July 6, 2000

For: A FRONT STRUCUTRE FOR A MOTOR VEHICLE

Attorney's Docket: 0615-102P

Box PATENT APPLICATION


Assistant Commissioner for Patents

Washington, D.C. 20231

S I R :


We enclose for filing a patent application comprising: Abstract (1 page); Specification (5 pages); 8 Claims; 2 sheets of drawing; an unexecuted Declaration and Power of Attorney form; an Information Disclosure Statement; and Form 1449 with copies of the cited documents. The priority of 9908690 France filed July 6, 1999 is claimed.

SCHWEITZER CORNMAN
GROSS & BONDELL LLP
230 Park Avenue
New York, New York 10169
Tel:(212)986-3377
Fax:(212)986-6126


Michael A. Cornman
Attorney for Applicant
Registration No. 20,672

I hereby certify that this paper or fee is being deposited with the U.S. Postal Service as Express Mail on the date indicated below and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Express Mail No.: EL369585367US
Mailing Date: July 6, 2000


Merle L. Cohn

07/06/00
jc841 U.S. PTO

jc675 U.S. PTO
09/610779
07/06/00

09610779, 070600

A FRONT STRUCTURE FOR A MOTOR VEHICLE

The present invention relates to a front structure for a motor vehicle:

BACKGROUND OF THE INVENTION

5 At the front of a conventional motor vehicle, there are generally to be found a bumper cross-member, an air inlet grille, and possibly a bottom part which can constitute a spoiler member, protection for the engine, or a bottom bar that acts in the event of a collision
10 with a pedestrian.

These various portions are made up of separate parts made of various materials which are assembled together on the vehicle, generally by means of screws, at predetermined anchor points.

15 These parts are independently designed so that each of them presents the required mechanical properties, depending on its own functions.

This gives rise to an assembly made up of these three parts which is relatively heavy, since each part on its own is required to perform the function assigned to it.
20

Japanese patent application 55 137 760 describes a structure having a cross-member for receiving a bumper.

Such a support structure does not itself comprise a bumper, with the bumper being constituted by a distinct part fitted thereto.
25

OBJECTS AND SUMMARY OF THE INVENTION

The present invention seeks to provide a novel front structure for a motor vehicle in which synergy is
30 implemented between the various parts so as to reduce the overall weight of the assembly.

Such a structure is designed to receive a shielding skin that covers it in part or in full.

The present invention provides a front structure for
35 a motor vehicle, the structure comprising at least one bumper cross-member and a grille, the structure being made a single piece of plastics material.

009510779-070600

In a particular embodiment, the structure includes a third portion on the opposite side of the grille to the cross-member.

In the structure of the invention, the continuous
5 link which exists between two adjacent parts enables each of the parts to confer stiffness to its neighbor(s) such that each part considered in isolation can be made to be less strong or less rigid than the corresponding part would need to be were it to be separate.

10 Furthermore, the fact of making a plurality of parts as a single piece gives rise to advantages which lead to lower cost price, both in manufacturing terms, given that a smaller quantity of plastics material is required for making the parts, and in assembly terms, given that the
15 one-piece structure requires a smaller amount of handling for installation in a vehicle.

The plastics structure of the invention can also be made to include specific functions merely by providing the corresponding shapes in the mold cavity.

20 In a particular embodiment of the invention, the grille is a grille for providing protection against chippings.

In another particular embodiment of the invention, the bumper cross-member includes shock absorbers
25 integrated therein the form of egg-shaped bulges or of a honeycomb.

In the embodiment in which the structure has a third portion, the third portion can constitute protection beneath the engine or a converging portion for guiding
30 the flow of air passing beneath the vehicle, or indeed a bottom bar which forms a portion that projects from the front of the vehicle for the purpose, in the event of a collision with a pedestrian, of striking the legs of the pedestrian below the knee at the same time as the bumper
35 strikes the legs above the knee.

In a particular embodiment, the structure receives a shielding skin which covers it in part or in full but

009020 62207960

which serves for the purposes of appearance only, with forces in the event of an impact being absorbed in full by the structure.

It is of interest to observe that the reduction in weight obtained by using the invention can also make it possible to use a shielding skin that is finer than in traditional structures because, in the invention, the skin is for the purposes of appearance only; with forces being absorbed in full by the structure.

BRIEF DESCRIPTION OF THE DRAWINGS

To make the invention better understood, there follows a description of two embodiments given as examples that do not limit the scope of the invention, and described with reference to the accompanying drawings, in which:

- Figure 1 is a three-quarters front perspective view of a structure constituting a first embodiment of the invention;
- Figure 2 is a three-quarters rear perspective view of the Figure 1 structure;
- Figure 3 is a three-quarters front perspective view of a structure constituting a second embodiment of the invention; and
- Figure 4 is a three-quarters rear perspective view of the Figure 3 structure.

MORE DETAILED DESCRIPTION

The structure of Figures 1 and 2 comprises a top bumper cross-member 1, an anti-chippings grille 2, and an under-engine protection 3 that is also used as a bottom bar.

The assembly is made as a single piece of plastics material, e.g. of polypropylene.

The top cross-member 1 is a channel section member. It is reinforced on its top face 4 by ribs 5 extending parallel to the direction of compression in the event of a front impact.

The front face 6 of the top cross-member is provided with projecting egg-shaped shock absorbers 7 which, like the ribs 5, are integrally molded with the remainder of the structure.

5 The anti-chipping grille 2 is a plate that is perforated in its central portion with openings 8 that allow a flow of air to pass to a radiator (not shown) mounted behind said grille 2. These openings 8 are of dimensions suitable for retaining the chippings which
10 might damage the radiator while the vehicle is running.

Since the same plastics material is used for making the entire structure, it is necessary, when dimensioning the rods 9 for making up the mesh of the grille, to allow for the flexibility of the plastics material which is
15 essential for enabling the cross-member to absorb impact shock.

In other words, during design of the part, it is important to avoid designing rods that are too thin, as might be appropriate for independent grilles of the prior
20 art, since such rods might deform under the impact of chippings and allow some of them to strike the radiator.

The under-engine protection 3 is shaped in such a manner as to extend beneath the engine (not shown) at the front of the vehicle for the purpose of protecting engine
25 components from possible impact against small objects carried by the flow of air passing beneath the vehicle.

This protection also serves to make the flow of air as laminar as possible so as to avoid slowing down displacement of the vehicle excessively.

30 Finally, it should be observed that the under-engine protection has a portion 10 that projects forwards. This projecting portion 10 is a bottom bar whose function is to constitute a point of impact against the legs of a pedestrian that is struck by the vehicle.

35 This bottom bar co-operates with the top cross-member 1 which usually strikes a leg of a pedestrian above the knee, whereas the bottom bar strikes the leg

0093020 64207900

beneath the knee. Combining these two points of impact serves to distribute force along the leg, and above all serves to avoid damaging the knee joint excessively.

5 The structure shown in Figures 1 and 2 is quite stiff overall, given the links between the portions extending across the entire width thereof, and this applies even though each portion, when considered in isolation, is lighter in weight than the equivalent part of a composite structure in which parts are assembled
10 together via localized fixing points.

The cross-member 1 receives a shielding skin P which is shown in part only and in highly diagrammatic manner in order to clarify the drawing.

15 In the embodiment of Figures 3 and 4, only the cross-member 1' differs from the preceding embodiment.

The cross-member 1' of this second embodiment has a honeycomb structure replacing the egg-shaped shock absorbers, as can be seen more clearly in Figure 4.

20 Naturally, the embodiments described above are not limiting in any way and could be modified in any desirable manner without thereby going beyond the ambit of the invention.

009020 6207950

~~CLAIMS~~

- 1/ A front structure for a motor vehicle, the structure comprising at least one bumper cross-member and a grille, the structure being made a single piece of plastics material.
- 2/ A structure according to claim 1, including a third portion on the opposite side of the grille to the cross-member.
- 3/ A structure according to claim 1, wherein the grille is an anti-chipping grille.
- 4/ A structure according to claim 1, wherein the bumper cross-member includes shock absorbers integrated therein the form of egg-shaped bulges or of a honeycomb.
- 5/ A structure according to claim 2, wherein the third portion consists in under-engine protection.
- 6/ A structure according to claim 2, wherein the third portion consists in a converging portion for guiding the flow of air passing beneath the vehicle.
- 7/ A structure according to claim 2, wherein the third portion consists in a bottom bar forming a portion for projecting from the front of the vehicle and having the function in the event of a collision with a pedestrian of striking the legs of the pedestrian beneath the knee at the same time as the bumper strikes the leg above the knee.
- 8/ A structure according to claim 1, receiving a shielding skin covering it in part or in full, and performing an appearance function only, with any force in the event of an impact being fully being absorbed by the structure.

A B S T R A C T

The invention provides a front structure for a motor vehicle, the structure comprising at least a bumper
5 cross-member and a grille. The structure being made as a single piece of plastics material.

09610779 070600

FIG. 1




FIG. 2




FIG. 3





FIG. 4



DECLARATION AND POWER OF ATTORNEY

As below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor [if only one name is listed below] or an original first and joint inventor [if plural names are listed below] of the subject matter which is claimed and for which a patent is sought on the invention entitled **A FRONT STRUCTURE FOR A MOTOR VEHICLE**, application for which [was filed in the United States Patent and Trademark Office on _____, Serial No. _____] [is enclosed herewith]. I hereby state that I authorized the filing of the specification.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, Section 1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate for the same invention having a filing date before that of the application on which priority is claimed:

PRIOR FOREIGN APPLICATION(S)

			Priority Claimed	
			Yes	No
9908690	France	06 July 1999		
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, Section 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.) (Filing Date) (Status-Patented, Pending, Abandoned)

And I hereby appoint Michael A. Cornman, Registration No. 20,672; Fritz L. Schweitzer, Jr., Registration No. 17,402; Meyer A. Gross, Registration No. 22,036; Jay A. Bondell, Esq., Registration No. 28,188; Fritz L. Schweitzer III, Registration No. 39,363; and Robert I. Pearlman, Registration No. 18,881 to prosecute this application and to transact all business in the Patent Office connected therewith, and I hereby request that all correspondence herein be directed to Michael A. Cornman, SCHWEITZER CORNMAN GROSS & BONDELL LLP, 230 Park Avenue, New York, New York 10169.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and, further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of inventor: Laurent POUGET

Inventor's signature: _____, Date: _____, 199

Residence: Oyonnax, France

Citizenship: French

Post Office Address: 92 Rue Alphonse Daudet, Veyziat 01100 Oyonnax, France

Full name of inventor: Thierry GOURLOT

Inventor's signature: _____, Date: _____, 199

Residence: Gray, France

Citizenship: French

Post Office Address: Grande Rue, Velesmes, 70100 Gray, France